



MEETS ASTM D4982-95:  
Flammability Potential Screening Analysis of Waste

MEETS ASTM D6523-00:  
Standard Guide for Alternative Daily Cover for  
Sanitary Landfills:

- Minimize Disease Vectors
- Control Leachate and Erosion
- Reduce Fire Hazard Potential
- Minimize Wind Blown Litter
- Reduce Noxious Odors.
- Provide an Aesthetic Appearance.
- Allow Accessibility Regardless of Weather

Biodegradable Non-Toxic  
Easy to load, mix and discharge.

### DESCRIPTION:

When combined with hydraulic mulch, Finn Enviro-Cap becomes a cost effective Alternative Daily Cover (ADC) that meets Federal requirements. It is a special blend of ingredients including a fire retardant and odor control agent. When mixed with water in a Finn landfill spray application unit, the spray on slurry is applied to the "open face" forming a cement-like crust. Enviro-Cap can be blended with any locally obtained paper or wood mulch. This combination of products can offer significant savings over other ADC materials and will cover more surface area per tank load.

\* LF 120: The Finn LF 120 was designed specifically for landfill use and can be towed behind any piece of heavy equipment. Use the LF 120 to spray on ADC, odor and dust control products as well as a wide variety of materials for turf development and erosion control. *Other size models are also available.*

### APPLICATION:

Mix one bag of Enviro-Cap with one bag of hydraulic mulch to 100 gallons of water in standard mechanical agitation spray on equipment. This combination of materials covers 900 square feet. A fully loaded Finn LF 120 landfill unit can cover up to 9000 square feet, while the process to load and discharge the slurry takes less than one hour.



### SMARTER WAYS TO WORK

9281 LeSaint Drive • Fairfield, OH 45014-5457 • Phone (513) 874-2818 • Fax (513) 874-2914  
Toll Free (800) 543-7166 • Parts (800) 229-8707 • E-mail: sales@finncorp.com  
Customer Service/Warranty (888) 382-1966