



EAGLE DIMENSIONS

A	Maximum operating height	98" (248.9 cm)
B	Overall height of loader	53.5" (135.9 cm)
C	Ground clearance	5.5" (14 cm)
D	Wheel base	30.5" (77.5 cm)
E	Overall length with no attachment	65.5" (166.4 cm)
F	Overall length with std. bucket	87.25" (221.6 cm)
G	Maximum roll back (self leveling)	30 degrees
H	Maximum down tilt	30 degrees
I	Reach with bucket	27.5" (69.9 cm)
J	Dump height (std. bucket)	52.25" (132.8 cm)
K	Bucket width (std. bucket)	40.5" (102.9 cm)
L	Loader width	
	Minimum (w/ opt. tires)	35.5" (90.2 cm)
	Maximum (w/ std. tires)	40.5" (102.9 cm)
M	Turning radius with bucket	55" (139.7 cm)
N	Turning radius without bucket	39.5" (100.3 cm)
O	Hinge pin height	71.75" (182.2 cm)

EAGLE SPECIFICATIONS

SPECIFICATIONS	204	244D	254
ENGINE	20 hp Kohler Command Pro	23.5 hp Caterpillar Diesel	25 hp Kohler Command Pro
FUEL TANK	11 US gallon capacity (41.5 liters)	11 US gallon capacity (41.5 liters)	11 US gallon capacity (41.5 liters)
OIL CAPACITY	2 quarts (1.9 liters)	3.5 quarts (3.3 liters)	2 quarts (1.9 liters)
HYDRAULIC SYSTEM	Parallel	Parallel	Parallel
PRESSURE	3000 psi (211 kg/cm ²)	3000 psi (211 kg/cm ²)	3000 psi (211 kg/cm ²)
FLOW	10 gpm (37.8 l/min) @ 3600 rpm	13.25 gpm (50.3 l/min) @ 3600 rpm	13.25 gpm (50.3 l/min) @ 3600 rpm
RESERVOIR	14.75 gallons (56 liters)	14.75 gallons (56 liters)	14.75 gallons (56 liters)
FILTER	10 micron hydraulic filter	10 micron hydraulic filter	10 micron hydraulic filter
ELECTRIC SYSTEM			
BATTERY	12 volt	12 volt	12 volt
INTERLOCKS	Aux. Valve neutral to start	Aux. Valve neutral to start	Aux. Valve neutral to start
WHEELS & TIRES			
STANDARD RIMS	9 x 7.00	9 x 7.00	9 x 7.00
STANDARD TIRES	18 x 8.50-8	18 x 9.50-8	18 x 9.50-8
DRIVE TRAIN	4 wheel motors	4 wheel motors	4 wheel motors
CONTROLS	Key, throttle, choke	Key, throttle	Key, throttle, choke
STEERING	Zero-turning radius	Zero-turning radius	Zero-turning radius
WEIGHT, NO ATTACHMENTS	1450 lbs. (658 kg)	1865 lbs. (846 kg)	1700 lbs. (807 kg)
WEIGHT, WITH STD. BUCKET	1565 lbs. (710 kg)	2022 lbs. (917 kg)	1895 lbs. (860 kg)
OPERATING CAPACITY			
WITH 200 LB. OPERATOR	475 lbs. (215 kg)	600 lbs. (273 kg)	550 lbs. (250 kg)